

TYRES

Product group	Tyres	
Item number	11166065	
Valid tyre size	315 / 70 R 22.5	
LI / SI / PR	154 / 151 M (156 / 150 M), 20 PR	
TL/TT	TL	
Brand	GoodTrip	
Tread pattern GHA20		





Notes and features

- The GoodTrip GHA20 is a radial truck tyre for the front or trailer axle for use in regional and long-distance transport.
- Its large contact area and angular tyre shoulder ensure very good driving stability and slow wear.
- The four wide circumferential grooves ensure excellent water drainage.
- Stone ejectors prevent tyre damage caused when small stones penetrate the tread.



Technical Informations

Item number	11166065		
EAN	8859625700053		
Valid tyre size	315 / 70 R 22.5		
LI / SI / PR	154 / 151 M (156 / 150 M), 20 PR		
TL/TT	TL		
Brand	GoodTrip		
Tread pattern	GHA20		
M+S	M+S		
3PMSF	3PMSF		
Axle position truck	FA/TR		
Rolling resistance	С		
Wet grip	В		
Rolling noise [db].	70		
Rolling noise level	A		
Antistatic	No		
Tyre colour	Black		
ECE regulation number	ECE 117,ECE 54		
Nettogewicht [kg] (gültig)	57,03		
Recommended rim size	9.00		
Permitted rim size	9.75		
Maximum air pressure [bar].	9,00		
Section width (mm)	312		
Outer diameter of tyre [mm].	1014		
Stat. radius (SLR) [mm]	469		
Rolling circumference [mm].	3187		
Tread depth (mm)	14,5		

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



E-Ready	No
---------	----

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 M	3750	130	Single	9,00	
156 M	4000	130	Single	9,00	
151 M	3450	130	Twin	9,00	
150 M	3350	130	Twin	9,00	