

TYRES

Product group	Tyres
Item number	11166080
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	154 / 151 M (157 / 154 L), 18 PR
TL/TT	TL
Brand	GoodTrip
Tread pattern	GMD30



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The GoodTrip GMD30 is a truck tyre for the drive axle for construction site vehicles.
- The tread pattern with pronounced blocks and grooves ensures very good driving and braking performance.
- The open tyre shoulder prevents the tyre from overheating.
- Its special tread compound and high tread depth make the tyre particularly durable.

Technical Informations

Item number	11166080
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	154 / 151 M (157 / 154 L), 18 PR
TL/TT	TL
Brand	GoodTrip
Tread pattern	GMD30
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	D
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	65,33
Recommended rim size	9.00
Permitted rim size	9.75
Maximum air pressure [bar].	8,30
Section width (mm)	312
Outer diameter of tyre [mm].	1076
Stat. radius (SLR) [mm]	500
Rolling circumference [mm].	3401
Tread depth (mm)	20,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 M	3750	130	Single	8,30	
157 L	4125	120	Single	8,30	
151 M	3450	130	Twin	8,30	
154 L	3750	120	Twin	8,30	