

TYRES

Product group	Tyres
Item number	11166115
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	160 K (158 L), 20 PR
TL/TT	TL
Brand	GoodTrip
Tread pattern	GHT50



Notes and features

- The GoodTrip GHT50 is a truck trailer tyre for regional transport.
- Its tread pattern with 4 circumferential grooves and a pronounced wide shoulder enables high load capacities and a long service life.
- The special rubber compound ensures low rolling resistance and noise and reduced fuel consumption.
- Stone ejectors in the V-shaped grooves prevent small stones from penetrating and causing tyre damage.

Technical Informations

Item number	11166115
EAN	8859625700213
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	160 K (158 L), 20 PR
TL/TT	TL
Brand	GoodTrip
Tread pattern	GHT50
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	B
Wet grip	B
Rolling noise [db].	69
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	67,50
Recommended rim size	11.75
Permitted rim size	12.25
Maximum air pressure [bar].	9,00
Section width (mm)	389
Outer diameter of tyre [mm].	1072
Stat. radius (SLR) [mm]	494
Rolling circumference [mm].	3363
Tread depth (mm)	15,5

E-Ready No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 K	4500	110	Single	9,00	
158 L	4250	120	Single	9,00	