

TYRES

Product group	Tyres
Item number	11285055
Valid tyre size	15.5 / 55 R 18
LI / SI / PR	138 E
TL/TT	TL
Brand	Dunlop
Tread pattern	SP PG7



Notes and features

- The Dunlop SP PG7 is an MPT radial tyre for construction machinery.
- The non-directional tread offers very good traction on difficult terrain.
- Due to the radial construction of the carcass and the flat tread contour, the ground pressure is evenly distributed and the ground is protected.

Technical Informations

Item number	11285055
EAN	5420005501930
Valid tyre size	15.5 / 55 R 18
LI / SI / PR	138 E
TL/TT	TL
Brand	Dunlop
Tread pattern	SP PG7
M+S	M+S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	47,00
Recommended rim size	11
Maximum air pressure [bar].	4,75
Section width (mm)	362
Outer diameter of tyre [mm].	892
Stat. radius (SLR) [mm]	409
Rolling circumference [mm].	2645
Tread depth (mm)	16,0
Tyre capacity 75% [ltr.]	84.75
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
138 E	2360	70		4,75	