

TYRES

Product group	Tyres
Item number	11285058
Valid tyre size	365 / 70 R 18
LI / SI / PR	146 A2 / 135 B
TL/TT	TL
Brand	Dunlop
Tread pattern	SP-T9



Bohnenkamp
Moving Professionals

Notes and features

- The Dunlop SP-T9 is an MPT radial tyre for wheel loaders, graders and other vehicles.
- It is ideal for mixed use on road and off-road.
- The tread blocks in the middle of the tread ensure driving comfort on the road, the studs on the outside of the tread allow very good traction.

Technical Informations

Item number	11285058
EAN	5420005503996
Valid tyre size	365 / 70 R 18
LI / SI / PR	146 A2 / 135 B
TL/TT	TL
Brand	Dunlop
Tread pattern	SP-T9
M+S	M+S
TRA Code	L2/E2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	54,00
Recommended rim size	11
Maximum air pressure [bar].	3,75
Section width (mm)	356
Outer diameter of tyre [mm].	975
Stat. radius (SLR) [mm]	438
Rolling circumference [mm].	2915
Tread depth (mm)	18,0
Tyre capacity 75% [ltr.]	105
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 A2	3000	10		3,75	
135 B	2180	50		3,75	