

TYRES

Product group	Tyres
Item number	11285070
Valid tyre size	335 / 80 R 20
LI / SI / PR	153 A2 / 149 K
TL/TT	TL
Brand	Dunlop
Tread pattern	SP-T9



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- The Dunlop SP-T9 is an MPT radial tyre for wheel loaders, graders and other vehicles.
- It is ideal for mixed use on road and off-road.
- The tread blocks in the middle of the tread ensure driving comfort on the road, the studs on the outside of the tread allow very good traction.

Technical Informations

Item number	11285070
EAN	4038526267894
Valid tyre size	335 / 80 R 20
LI / SI / PR	153 A2 / 149 K
TL/TT	TL
Brand	Dunlop
Tread pattern	SP-T9
M+S	M+S
TRA Code	L2/E2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	57,00
Recommended rim size	11.00
Maximum air pressure [bar].	4,50
Section width (mm)	323
Outer diameter of tyre [mm].	1035
Stat. radius (SLR) [mm]	482
Rolling circumference [mm].	3130
Tread depth (mm)	19,0
Tyre capacity 75% [ltr.]	103
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A2	3650	10		4,50	
149 K	3250	110		4,50	