

## TYRES

Product group	Tyres
Item number	11285075
Valid tyre size	365 / 80 R 20
LI / SI / PR	153 A2 / 141 B
TL/TT	TL
Brand	Dunlop
Tread pattern	SP-T9



## Notes and features

- The Dunlop SP-T9 is an MPT radial tyre for wheel loaders, graders and other vehicles.
- It is ideal for mixed use on road and off-road.
- The tread blocks in the middle of the tread ensure driving comfort on the road, the studs on the outside of the tread allow very good traction.

## Technical Informations

Item number	11285075
EAN	5420005504009
Valid tyre size	365 / 80 R 20
LI / SI / PR	153 A2 / 141 B
TL/TT	TL
Brand	Dunlop
Tread pattern	SP-T9
M+S	M+S
TRA Code	L2/E2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	64,00
Recommended rim size	11
Permitted rim size	12, 11-20SDC, 12-20SDC
Maximum air pressure [bar].	3,75
Section width (mm)	360
Outer diameter of tyre [mm].	1092
Stat. radius (SLR) [mm]	493
Rolling circumference [mm].	3285
Tread depth (mm)	20,0
Tyre capacity 75% [ltr.]	175
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A2	3650	10		3,75	
141 B	2575	50		3,75	