Bohnenkamp Moving Professionals

20.09.2024

TYRES

Product group	Tyres
Item number	11285090
Valid tyre size	405 / 70 R 20
LI / SI / PR	155 A2 / 143 B
TL/TT	TL
Brand	Dunlop
Tread pattern	SP-T9



Notes and features

- The Dunlop SP-T9 is an MPT radial tyre for wheel loaders, graders and other vehicles.
- It is ideal for mixed use on road and off-road.
- The tread blocks in the middle of the tread ensure driving comfort on the road, the studs on the outside of the tread allow very good traction.

Bohnenkamp Moving Professionals

Technical Informations

Item number	11285090
EAN	5420005504054
EAN	5420005504054
Valid tyre size	405 / 70 R 20
LI / SI / PR	155 A2 / 143 B
TL/TT	TL
Brand	Dunlop
Tread pattern	SP-T9
M+S	M+S
TRA Code	L2/E2
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	70,00
Maximum air pressure [bar].	3,75
Section width (mm)	403
Outer diameter of tyre [mm].	1093
Stat. radius (SLR) [mm]	487
Rolling circumference [mm].	3240
Tread depth (mm)	19,0
Tyre capacity 75% [ltr.]	160
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A2	3875	10		3,75	
143 B	2725	50		3,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.