

TYRES

Product group	Tyres
Item number	11285091
Valid tyre size	405 / 70 R 20
LI / SI / PR	168 A2 / 152 J
TL/TT	TL
Brand	Dunlop
Tread pattern	SP-T9



Bohnenkamp
Moving Professionals

Notes and features

- The Dunlop SP-T9 is an MPT radial tyre for wheel loaders, graders and other vehicles.
- It is ideal for mixed use on road and off-road.
- The tread blocks in the middle of the tread ensure driving comfort on the road, the studs on the outside of the tread allow very good traction.

Technical Informations

Item number	11285091
EAN	5420005504078
Valid tyre size	405 / 70 R 20
LI / SI / PR	168 A2 / 152 J
TL/TT	TL
Brand	Dunlop
Tread pattern	SP-T9
M+S	M+S
TRA Code	L2/E2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	73,00
Recommended rim size	13
Maximum air pressure [bar].	6,00
Section width (mm)	401
Outer diameter of tyre [mm].	1094
Stat. radius (SLR) [mm]	495
Rolling circumference [mm].	3230
Tread depth (mm)	20,0
Tyre capacity 75% [ltr.]	160
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 A2	5600	10		6,00	
152 J	3550	100		6,00	