

TYRES

Product group	Tyres
Item number	11285100
Valid tyre size	405 / 70 R 24
LI / SI / PR	168 A2 / 152 J
TL/TT	TL
Brand	Dunlop
Tread pattern	SP-T9



Bohnenkamp
Moving Professionals



Notes and features

- The Dunlop SP-T9 is an MPT radial tyre for wheel loaders, graders and other vehicles.
- It is ideal for mixed use on road and off-road.
- The tread blocks in the middle of the tread ensure driving comfort on the road, the studs on the outside of the tread allow very good traction.

Technical Informations

Item number	11285100
EAN	4038526206527
Valid tyre size	405 / 70 R 24
LI / SI / PR	168 A2 / 152 J
TL/TT	TL
Brand	Dunlop
Tread pattern	SP-T9
M+S	M+S
TRA Code	L2/E2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	88,00
Recommended rim size	13.00
Permitted rim size	13.00SDC
Maximum air pressure [bar].	5,00
Section width (mm)	403
Outer diameter of tyre [mm].	1187
Stat. radius (SLR) [mm]	538
Rolling circumference [mm].	3545
Tread depth (mm)	22,0
Tyre capacity 75% [ltr.]	173
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 A2	5600	10		5,00	
152 J	3550	100		5,00	