

TYRES

Product group	Tyres
Item number	11285110
Valid tyre size	455 / 70 R 24
LI / SI / PR	174 A2 / 154 G
TL/TT	TL
Brand	Dunlop
Tread pattern	SP-T9



Bohnenkamp
Moving Professionals



Notes and features

- The Dunlop SP-T9 is an MPT radial tyre for wheel loaders, graders and other vehicles.
- It is ideal for mixed use on road and off-road.
- The tread blocks in the middle of the tread ensure driving comfort on the road, the studs on the outside of the tread allow very good traction.

Technical Informations

Item number	11285110
EAN	5420005504122
Valid tyre size	455 / 70 R 24
LI / SI / PR	174 A2 / 154 G
TL/TT	TL
Brand	Dunlop
Tread pattern	SP-T9
M+S	M+S
TRA Code	L2/E2
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	109,00
Recommended rim size	DW14L
Permitted rim size	DW15L
Maximum air pressure [bar].	3,75
Section width (mm)	442
Outer diameter of tyre [mm].	1247
Stat. radius (SLR) [mm]	576
Rolling circumference [mm].	3745
Tread depth (mm)	23,0
Tyre capacity 75% [litr.]	81.75
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
174 A2	6700	10		3,75	
154 G	3750	90		3,75	