

## TYRES

Product group	Tyres
Item number	11366100
Valid tyre size	205 / 65 R 17.5
LI / SI / PR	129 / 127 J (132 / 132 G), 16 PR
TL/TT	TL
Brand	Linglong
Tread pattern	LFL866



Bohnenkamp  
■ ■ ● Moving Professionals

## Notes and features

- The Ling Long LFL866 is a truck tyre for steer and trailer axles used in long-distance and regional transport.
- Its extra-wide tread pattern design guarantees even wear and a long service life.
- Zigzag-shaped longitudinal grooves ensure very good driving characteristics.

## Technical Informations

Item number	11366100
EAN	4040658087776
Valid tyre size	205 / 65 R 17.5
LI / SI / PR	129 / 127 J (132 / 132 G), 16 PR
TL/TT	TL
Brand	Linglong
Tread pattern	LFL866
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/TR
Rolling resistance	E
Wet grip	B
Rolling noise [db].	72
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	25,80
Recommended rim size	6.00
Permitted rim size	6.75
Maximum air pressure [bar].	9,00
Section width (mm)	205
Outer diameter of tyre [mm].	711
Stat. radius (SLR) [mm]	334
Dynamic radius [mm]	342.87
Rolling circumference [mm].	2154

---

Tread depth (mm)	12,5
E-Ready	No

---

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
129 J	1850	100	Single	9,00	
132 G	2000	90	Single	9,00	
127 J	1750	100	Twin	9,00	
132 G	2000	90	Twin	9,00	