

TYRES

| | |
|-----------------|-----------------|
| Product group | Tyres |
| Item number | 11366115 |
| Valid tyre size | 445 / 45 R 19.5 |
| LI / SI / PR | 160 J, 20 PR |
| TL/TT | TL |
| Brand | Linglong |
| Tread pattern | T820 |



Notes and features

- The Ling Long T820 is a truck tyre for long-haul transport on motorways and well-maintained roads.
- The tyre is characterised by a low rolling resistance resulting in low fuel consumption.
- It provides very good driving stability even on wet roads.

Technical Informations

| | |
|------------------------------|-----------------|
| Item number | 11366115 |
| EAN | 8859291423348 |
| Valid tyre size | 445 / 45 R 19.5 |
| LI / SI / PR | 160 J, 20 PR |
| TL/TT | TL |
| Brand | Linglong |
| Tread pattern | T820 |
| M+S | M+S |
| 3PMSF | 3PMSF |
| Axle position truck | TR |
| Rolling resistance | C |
| Wet grip | B |
| Rolling noise [db]. | 73 |
| Rolling noise level | B |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54,ECE 117 |
| Nettogewicht [kg] (gültig) | 65,24 |
| Recommended rim size | 15.00 |
| Permitted rim size | 14.00 |
| Maximum air pressure [bar]. | 9,00 |
| Section width (mm) | 446 |
| Outer diameter of tyre [mm]. | 895 |
| Stat. radius (SLR) [mm] | 422 |
| Rolling circumference [mm]. | 2711 |
| Tread depth (mm) | 15,5 |

E-Ready

No

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 160 J | 4500 | 100 | Single | 9,00 | |