

TYRES

Product group	Tyres
Item number	11366135
Valid tyre size	315 / 60 R 22.5
LI / SI / PR	152 / 148 L, 16 PR
TL/TT	TL
Brand	Linglong
Tread pattern	KTD300



Notes and features

- The Ling Long KTD300 is a truck tyre for drive axles in regional transportation.
- Its optimised shoulder construction provides improved protection against damages.
- The tyre is very wear resistant and guarantees good grip and stability over its entire service life.

Technical Informations

Item number	11366135
EAN	8859291423027
Valid tyre size	315 / 60 R 22.5
LI / SI / PR	152 / 148 L, 16 PR
TL/TT	TL
Brand	Linglong
Tread pattern	KTD300
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	D
Wet grip	B
Rolling noise [db].	75
Rolling noise level	C
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	60,64
Recommended rim size	9.75
Permitted rim size	9.00
Maximum air pressure [bar].	9,00
Section width (mm)	313
Outer diameter of tyre [mm].	950
Stat. radius (SLR) [mm]	445
Rolling circumference [mm].	2878
Tread depth (mm)	19,5

E-Ready	No
---------	----

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 L	3550	120	Single	9,00	
148 L	3150	120	Twin	9,00	