

TYRES

Product group	Tyres
Item number	11366145
Valid tyre size	385 / 55 R 22.5
LI / SI / PR	160 K (158 L), 20 PR
TL/TT	TL
Brand	Linglong
Tread pattern	KTS300



 **LINGLONG TIRE**

Notes and features

- The Ling Long KTS300 is a truck steering axle tyre for use in regional transport.
- Its optimised shoulder construction provides improved protection against damages to the tyre shoulder.
- Stone deflectors protect the tread pattern from damages by preventing small stones from penetrating the tread.
- The tyre is very wear resistant and guarantees good grip and stability over its entire service life.

Technical Informations

Item number	11366145
EAN	8859291423911
Valid tyre size	385 / 55 R 22.5
LI / SI / PR	160 K (158 L), 20 PR
TL/TT	TL
Brand	Linglong
Tread pattern	KTS300
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/TR
Rolling resistance	D
Wet grip	C
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	70,74
Recommended rim size	12.25
Permitted rim size	11.75
Maximum air pressure [bar].	9,00
Section width (mm)	386
Outer diameter of tyre [mm].	996
Stat. radius (SLR) [mm]	464
Rolling circumference [mm].	3017
Tread depth (mm)	13,5

E-Ready	No
---------	----

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 K	4500	110	Single	9,00	
158 L	4250	120	Single	9,00	