

TYRES

Product group	Tyres	
Item number	11366515	
Valid tyre size	445 / 45 R 19.5	
LI / SI / PR	164 D, 24 PR	
TL/TT	TL	
Brand	Linglong	
Tread pattern	KXA408	



Technical Informations

Item number	11366515
EAN	4040658091070
Valid tyre size	445 / 45 R 19.5
LI / SI / PR	164 D, 24 PR
TL/TT	TL
Brand	Linglong
Tread pattern	KXA408
M+S	M+S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Nettogewicht [kg] (gültig)	70,00
Recommended rim size	15.00
Permitted rim size	14.00
Maximum air pressure [bar].	9,00
Section width (mm)	446
Outer diameter of tyre [mm].	895
Stat. radius (SLR) [mm]	422
Rolling circumference [mm].	2712
Tread depth (mm)	16,0
E-Ready	No

Load capacity

Inde	x Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164	D 5000	65		6,00	