

## **TYRES**

Product group	Tyres	
Item number	11384100	
Valid tyre size	405 / 70 R 18	
LI / SI / PR	153 A2 / 141 B	
TL/TT	TL	
Brand	Linglong	
Tread pattern	LR400	



## Notes and features

- The Ling Long LR400 is a very cost-effective EM radial tyre for telescopic loaders, backhoes und mini wheel loaders.
- Its strong rubber compound provides efficient puncture resistance and a long service life.
- The special shoulder design enables even wear and good puncture and impact resistance.
- The circumferential strip of tread blocks in the tread centre guarantees very good steering and wear resistance



## **Technical Informations**

Item number	11384100
EAN	4040658089534
Valid tyre size	405 / 70 R 18
LI / SI / PR	153 A2 / 141 B
TL/TT	TL
Brand	Linglong
Tread pattern	LR400
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	57,10
Recommended rim size	13
Permitted rim size	11, 12
Maximum air pressure [bar].	3,80
Section width (mm)	407
Outer diameter of tyre [mm].	1025
Stat. radius (SLR) [mm]	452
Rolling circumference [mm].	3048
Tread depth (mm)	23,0
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A2	3650	10		3,80	
141 B	2575	50		3,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.