

TYRES

Product group	Tyres
Item number	11384110
Valid tyre size	405 / 70 R 20
LI / SI / PR	155 A2
TL/TT	TL
Brand	Linglong
Tread pattern	LR400



Notes and features

- The Ling Long LR400 is a very cost-effective EM radial tyre for telescopic loaders, backhoes und mini wheel loaders.
- Its strong rubber compound provides efficient puncture resistance and a long service life.
- The special shoulder design enables even wear and good puncture and impact resistance.
- The circumferential strip of tread blocks in the tread centre guarantees very good steering and wear resistance

Technical Informations

Item number	11384110
EAN	4040658089541
Valid tyre size	405 / 70 R 20
LI / SI / PR	155 A2
TL/TT	TL
Brand	Linglong
Tread pattern	LR400
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	61,10
Recommended rim size	13
Permitted rim size	11, 12, 14
Maximum air pressure [bar].	3,80
Section width (mm)	407
Outer diameter of tyre [mm].	1076
Stat. radius (SLR) [mm]	475
Rolling circumference [mm].	3203
Tread depth (mm)	29,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A2	3875	10		3,80	
143 B	2725	50		3,80	