

## TYRES

Product group	Tyres
Item number	11384120
Valid tyre size	500 / 70 R 24
LI / SI / PR	164 A / 164 B
TL/TT	TL
Brand	Linglong
Tread pattern	LR400



## Notes and features

- The Ling Long LR400 is a very cost-effective EM radial tyre for telescopic loaders, backhoes und mini wheel loaders.
- Its strong rubber compound provides efficient puncture resistance and a long service life.
- The special shoulder design enables even wear and good puncture and impact resistance.
- The circumferential strip of tread blocks in the tread centre guarantees very good steering and wear resistance

## Technical Informations

Item number	11384120
EAN	6959956756254
Valid tyre size	500 / 70 R 24
LI / SI / PR	164 A / 164 B
TL/TT	TL
Brand	Linglong
Tread pattern	LR400
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	110,08
Recommended rim size	DW16L
Permitted rim size	DW15L
Maximum air pressure [bar].	4,00
Section width (mm)	503
Outer diameter of tyre [mm].	1310
Stat. radius (SLR) [mm]	592
Rolling circumference [mm].	3873
Tread depth (mm)	28,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 A8	5000	40		4,00	
164 B	5000	50		4,00	