Bohnenkamp Moving Professionals

17.11.2024

TYRES

Product group	Tyres	
Item number	12011508	
Valid tyre size	41 / 18 LL x 22.5	
LI / SI / PR	179 A2, 20 PR	
TL/TT	TL	
Brand	Galaxy	
Tread pattern	Turf Special	





Notes and features

- Tyre specially designed for lawns, golf courses and delicate subsoils.
- Principal use on machinery for professional lawn care and landscaping.
- Tread pattern is particularly gentle to the soil due to large tread pattern blocks and rounded shoulders.
- Offers flotation properties such as low ground pressure and a wide contact area.

Bohnenkamp Moving Professionals

Technical Informations

Item muchen	10011500
Item number	12011508
EAN	8903635021452
Valid tyre size	41 / 18 LL x 22.5
LI / SI / PR	179 A2, 20 PR
TL/TT	ть
Brand	Galaxy
Tread pattern	Turf Special
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	58,20
Recommended rim size	14
Maximum air pressure [bar].	6,90
Section width (mm)	457
Outer diameter of tyre [mm].	1030
Stat. radius (SLR) [mm]	476
Rolling circumference [mm].	3066
Tread depth (mm)	9,5
Guarantee period	5 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
179 A2	7750	10		6,90	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.