

TYRES

Product group	Tyres	
Item number	12015180	
Valid tyre size	29 x 12.50 - 15	
LI / SI / PR	107 B, 8 PR	
TL/TT	TL	
Brand	Galaxy	
Tread pattern	Super Trencher	





Notes and features

- The Galaxy Super Trencher I-3 is an all-purpose small tyre.
- The flat lugs enable optimal use on municipal and other small tractors.
- The reinforced sidewall reliably protects the tyre from damages.



Technical Informations

Item number	12015180
EAN	8903635018766
Valid tyre size	29 x 12.50 - 15
LI / SI / PR	107 B, 8 PR
TL/TT	TL
Brand	Galaxy
Tread pattern	Super Trencher
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	22,54
Recommended rim size	10
Maximum air pressure [bar].	2,75
Section width (mm)	318
Outer diameter of tyre [mm].	750
Stat. radius (SLR) [mm]	344
Tread depth (mm)	17,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
107 B	975	50		2,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.