

## **TYRES**

Product group	Tyres
Item number	12426005
Valid tyre size	280 / 70 R 16
LI / SI / PR	112 A8 / 109 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker





## **Notes and features**

- Maximum traction due to optimised lug shape.
- Low soil compaction due to flat tread pattern.
- Good ride comfort due to high deflection zone.
- Long service life.



## **Technical Informations**

Item number	12426005
item number	12420005
EAN	3528707893536
Valid tyre size	280 / 70 R 16
LI / SI / PR	112 A8 / 109 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	24,00
Recommended rim size	W9
Permitted rim size	W8L, W8, W10L
Maximum air pressure [bar].	2,40
Section width (mm)	263
Outer diameter of tyre [mm].	799
Stat. radius (SLR) [mm]	358
Rolling circumference [mm].	2373
Tread depth (mm)	29,0
Number of lugs	16x2
Tyre capacity 75% [ltr.]	50
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
112 A8	1120	40		2,40	
109 B	1030	50		2,40	