

TYRES

Product group	Tyres	
Item number	12426074	
Valid tyre size	360 / 70 R 20	
LI / SI / PR	129 A8 / 126 B	
TL/TT	TL	
Brand	Kleber	
Tread pattern	Fitker	





Notes and features

- Maximum traction due to optimised lug shape.
- Low soil compaction due to flat tread pattern.
- Good ride comfort due to high deflection zone.
- Long service life.



Technical Informations

Item number	12426074
EAN	3528703569824
Valid tyre size	360 / 70 R 20
LI / SI / PR	129 A8 / 126 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	50,40
Recommended rim size	11
Permitted rim size	9, 10, 12
Maximum air pressure [bar].	2,40
Section width (mm)	366
Outer diameter of tyre [mm].	1052
Stat. radius (SLR) [mm]	466
Rolling circumference [mm].	3144
Tread depth (mm)	41,0
Number of lugs	17x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
129 A8	1850	40		2,40	
126 B	1700	50		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.