

TYRES

Product group	Tyres
Item number	12426094
Valid tyre size	280 / 85 R 24
LI / SI / PR	115 A8 / 112 B
TL/TT	TL
Brand	Kleber
Tread pattern	Traker





Notes and features

- Very good traction through high tread lugs.
- Good self-cleaning.

• Even pressure distribution due to flat tread pattern.



Technical Informations

Item number	12426094
EAN	3528701617671
Valid tyre size	280 / 85 R 24
Alternative size 1	11.2R24
LI / SI / PR	115 A8 / 112 B
TL/TT	TL
Brand	Kleber
Tread pattern	Traker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	39,00
Recommended rim size	10
Permitted rim size	9
Maximum air pressure [bar].	1,60
Section width (mm)	288
Outer diameter of tyre [mm].	1100
Stat. radius (SLR) [mm]	493
Rolling circumference [mm].	3267
Tread depth (mm)	37,0
Number of lugs	19x2
Lug width (mm)	35
Tyre capacity 75% [ltr.]	89
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
115 A8	1215	40		1,60	
112 B	1120	50		1,60	