

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 12426152 |
| Valid tyre size | 420 / 70 R 24 |
| LI / SI / PR | 136 A8 / 136 B |
| TL/TT | TL |
| Brand | Kleber |
| Tread pattern | Fitker |



Bohnenkamp
■ ■ ● Moving Professionals

**Kleber**

Notes and features

- Maximum traction due to optimised lug shape.
- Low soil compaction due to flat tread pattern.
- Good ride comfort due to high deflection zone.
- Long service life.

Technical Informations

| | |
|------------------------------|------------------|
| Item number | 12426152 |
| EAN | 3528704728060 |
| Valid tyre size | 420 / 70 R 24 |
| LI / SI / PR | 136 A8 / 136 B |
| TL/TT | TL |
| Brand | Kleber |
| Tread pattern | Fitker |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 75,00 |
| Recommended rim size | W13 |
| Permitted rim size | W12, DW14L, W14L |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 437 |
| Outer diameter of tyre [mm]. | 1255 |
| Stat. radius (SLR) [mm] | 563 |
| Rolling circumference [mm]. | 3727 |
| Tread depth (mm) | 43,0 |
| Number of lugs | 19x2 |
| Tyre capacity 75% [litr.] | 203 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 136 A8 | 2240 | 40 | | 2,40 | |
| 136 B | 2240 | 50 | | 2,40 | |