

TYRES

Product group	Tyres
Item number	12426152
Valid tyre size	420 / 70 R 24
LI / SI / PR	136 A8 / 136 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker



Bohnenkamp
■ ■ ● Moving Professionals

**Kleber**

Notes and features

- Maximum traction due to optimised lug shape.
- Low soil compaction due to flat tread pattern.
- Good ride comfort due to high deflection zone.
- Long service life.

Technical Informations

Item number	12426152
EAN	3528704728060
Valid tyre size	420 / 70 R 24
LI / SI / PR	136 A8 / 136 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	75,00
Recommended rim size	W13
Permitted rim size	W12, DW14L, W14L
Maximum air pressure [bar].	2,40
Section width (mm)	437
Outer diameter of tyre [mm].	1255
Stat. radius (SLR) [mm]	563
Rolling circumference [mm].	3727
Tread depth (mm)	43,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	203
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
136 A8	2240	40		2,40	
136 B	2240	50		2,40	