

TYRES

Product group	Tyres
Item number	12426300
Valid tyre size	420 / 70 R 28
LI / SI / PR	133 A8 / 133 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker



Bohnenkamp
■ ■ ● Moving Professionals

**Kleber**

Notes and features

- Maximum traction due to optimised lug shape.
- Low soil compaction due to flat tread pattern.
- Good ride comfort due to high deflection zone.
- Long service life.

Technical Informations

Item number	12426300
EAN	3528706550287
Valid tyre size	420 / 70 R 28
LI / SI / PR	133 A8 / 133 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	83,00
Recommended rim size	13
Permitted rim size	12, 14
Maximum air pressure [bar].	1,60
Section width (mm)	439
Outer diameter of tyre [mm].	1366
Stat. radius (SLR) [mm]	608
Rolling circumference [mm].	4050
Tread depth (mm)	42,0
Number of lugs	20x2
Lug width (mm)	38
Tyre capacity 75% [ltr.]	231
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 A8	2060	40		1,60	
133 B	2060	50		1,60	