

TYRES

Product group	Tyres
Item number	12426339
Valid tyre size	600 / 70 R 30
LI / SI / PR	152 A8 / 149 D
TL/TT	TL
Brand	Kleber
Tread pattern	Topker



Kleber

Notes and features

- Large volume tyre for high-performance tractors.
- Optimally suitable for ploughing.
- Can be used with low inflation pressures.
- Very good traction.

Technical Informations

Item number	12426339
EAN	3528708119994
Valid tyre size	600 / 70 R 30
LI / SI / PR	152 A8 / 149 D
TL/TT	TL
Brand	Kleber
Tread pattern	Topker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	176,00
Recommended rim size	20
Permitted rim size	18
Maximum air pressure [bar].	1,60
Section width (mm)	612
Outer diameter of tyre [mm].	1590
Stat. radius (SLR) [mm]	705
Rolling circumference [mm].	4709
Tread depth (mm)	51,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	456
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 A8	3550	40		1,60	
149 D	3250	65		1,60	