

TYRES

Product group	Tyres
Item number	12426339
Valid tyre size	600 / 70 R 30
LI / SI / PR	152 A8 / 149 D
TL/TT	TL
Brand	Kleber
Tread pattern	Topker





Notes and features

- Large volume tyre for high-performance tractors.
- Optimally suitable for ploughing.

- Can be used with low inflation pressures.
- Very good traction.



Technical Informations

Item number	12426339
EAN	3528708119994
Valid tyre size	600 / 70 R 30
LI / SI / PR	152 A8 / 149 D
TL/TT	TL
Brand	Kleber
Tread pattern	Topker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	176,00
Recommended rim size	20
Permitted rim size	18
Maximum air pressure [bar].	1,60
Section width (mm)	612
Outer diameter of tyre [mm].	1590
Stat. radius (SLR) [mm]	705
Rolling circumference [mm].	4709
Tread depth (mm)	51,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	456
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 A8	3550	40		1,60	
149 D	3250	65		1,60	