

TYRES

Product group	Tyres	
Item number	12426372	
Valid tyre size	210 / 95 R 32	
LI / SI / PR	114 A8 / 114 B	
TL/TT	TL	
Brand	Kleber	
Tread pattern	Super 3	





Notes and features

- Row crop tyre for tractors within performance range of 80
 200 hp.
- Excellent growth of row crops: the lug shoulders protect plant stocks.
- Robustness and service life: high load capacity. Even rolling of the tread lugs.
- Time saving: for speeds of up to 50 km/h.



Technical Informations

Item number	12426372
EAN	3528702317075
Valid tyre size	210 / 95 R 32
Alternative size 1	8.3R32
LI / SI / PR	114 A8 / 114 B
TL/TT	TL
Brand	Kleber
Tread pattern	Super 3
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	36,90
Recommended rim size	7
Maximum air pressure [bar].	2,40
Section width (mm)	212
Outer diameter of tyre [mm].	1212
Stat. radius (SLR) [mm]	569
Rolling circumference [mm].	3638
Tread depth (mm)	29,0
Number of lugs	28x2
Tyre capacity 75% [ltr.]	67
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
114 A8	1180	40		2,40	
114 B	1180	50		2,40	