

## **TYRES**

Product group	Tyres
Item number	12426457
Valid tyre size	520 / 70 R 34
LI / SI / PR	148 A8 / 148 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker





## **Notes and features**

- Maximum traction due to optimised lug shape.
- Low soil compaction due to flat tread pattern.
- Good ride comfort due to high deflection zone.
- Long service life.



## **Technical Informations**

Item number	12426457
EAN	3528702895733
Valid tyre size	520 / 70 R 34
LI / SI / PR	148 A8 / 148 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	147,00
Recommended rim size	16
Permitted rim size	15, 18
Maximum air pressure [bar].	1,60
Section width (mm)	535
Outer diameter of tyre [mm].	1654
Stat. radius (SLR) [mm]	734
Rolling circumference [mm].	4901
Tread depth (mm)	51,0
Number of lugs	20x2
Lug width (mm)	50
Tyre capacity 75% [ltr.]	422
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 A8	3150	40		1,60	
148 B	3150	50		1,60	