Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	12426543
Valid tyre size	320 / 85 R 36
LI / SI / PR	128 A8 / 125 B
TL/TT	TL
Brand	Kleber
Tread pattern	Traker



Notes and features

- Very good traction through high tread lugs.
- Good self-cleaning.

• Even pressure distribution due to flat tread pattern.

Bohnenkamp Moving Professionals

Technical Informations

Item number	12426543
EAN	3528701617794
Valid tyre size	320 / 85 R 36
Alternative size 1	12.4R36
LI / SI / PR	128 A8 / 125 B
TL/TT	TL
Brand	Kleber
Tread pattern	Traker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	72,00
Recommended rim size	11
Permitted rim size	10
Maximum air pressure [bar].	1,60
Section width (mm)	323
Outer diameter of tyre [mm].	1461
Stat. radius (SLR) [mm]	667
Rolling circumference [mm].	4357
Tread depth (mm)	43,0
Number of lugs	24x2
Tyre capacity 75% [ltr.]	165
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
128 A8	1800	40		1,60	
125 B	1650	50		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.