

TYRES

Product group	Tyres
Item number	12426615
Valid tyre size	520 / 70 R 38
LI / SI / PR	150 A8 / 150 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker





Notes and features

- Maximum traction due to optimised lug shape.
- Low soil compaction due to flat tread pattern.
- Good ride comfort due to high deflection zone.
- Long service life.



Technical Informations

Item number	12426615
EAN	3528707595560
Valid tyre size	520 / 70 R 38
LI / SI / PR	150 A8 / 150 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	160,80
Recommended rim size	16
Permitted rim size	15, 18
Maximum air pressure [bar].	1,60
Section width (mm)	536
Outer diameter of tyre [mm].	1765
Stat. radius (SLR) [mm]	783
Rolling circumference [mm].	5228
Tread depth (mm)	51,0
Number of lugs	21x2
Lug width (mm)	48
Tyre capacity 75% [ltr.]	464
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 A8	3350	40		1,60	
150 B	3350	50		1,60	