

TYRES

Product group	Tyres
Item number	12426615
Valid tyre size	520 / 70 R 38
LI / SI / PR	150 A8 / 150 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker



Bohnenkamp
■ ■ ● Moving Professionals

**Kleber**

Notes and features

- Maximum traction due to optimised lug shape.
- Low soil compaction due to flat tread pattern.
- Good ride comfort due to high deflection zone.
- Long service life.

Technical Informations

Item number	12426615
EAN	3528707595560
Valid tyre size	520 / 70 R 38
LI / SI / PR	150 A8 / 150 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	160,80
Recommended rim size	16
Permitted rim size	15, 18
Maximum air pressure [bar].	1,60
Section width (mm)	536
Outer diameter of tyre [mm].	1765
Stat. radius (SLR) [mm]	783
Rolling circumference [mm].	5228
Tread depth (mm)	51,0
Number of lugs	21x2
Lug width (mm)	48
Tyre capacity 75% [ltr.]	464
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 A8	3350	40		1,60	
150 B	3350	50		1,60	