

TYRES

Product group	Tyres
Item number	12426654
Valid tyre size	620 / 70 R 42
LI / SI / PR	160 A8 / 160 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker



Bohnenkamp
■ ■ ● Moving Professionals

**Kleber**

Notes and features

- Maximum traction due to optimised lug shape.
- Low soil compaction due to flat tread pattern.
- Good ride comfort due to high deflection zone.
- Long service life.

Technical Informations

Item number	12426654
EAN	3528701016412
Valid tyre size	620 / 70 R 42
LI / SI / PR	160 A8 / 160 B
TL/TT	TL
Brand	Kleber
Tread pattern	Fitker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	238,00
Recommended rim size	20
Permitted rim size	18
Maximum air pressure [bar].	1,60
Section width (mm)	631
Outer diameter of tyre [mm].	1952
Stat. radius (SLR) [mm]	866
Rolling circumference [mm].	5783
Tread depth (mm)	56,0
Number of lugs	20x2
Lug width (mm)	56
Tyre capacity 75% [ltr.]	658
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 A8	4500	40		1,60	
160 B	4500	50		1,60	