

## **TYRES**

Product group	Tyres
Item number	12426775
Valid tyre size	230 / 95 R 36
LI / SI / PR	133 A8 / 130 D
TL/TT	TL
Brand	Kleber
Tread pattern	Cropker





## Notes and features

- The Kleber Cropker is a premium crop tyre for tractors in the 80-200 hp performance range.
- Compared with its predecessor, the Kleber Super 3, the Cropker offers a higher load capacity and the double identifier D/A8.
- It can be used as a FRT (Free Rolling Tyre) on towed vehicles with with a load surcharge of up to 20% at 40 km/h.
- Thanks to the special root-friendly lug shoulders, plants in row crops are optimally protected.
- Its tread pattern reinforced in the centre of the tread provides improved driving and steering precision and longer mileage.
- Due to the shape of the lugs and the spaces between them, the tyre offers very good self-cleaning properties.



## **Technical Informations**

Item number	12426775
EAN	3528702394823
Valid tyre size	230 / 95 R 36
Alternative size 1	9.5R36
LI / SI / PR	133 A8 / 130 D
TL/TT	TL
Brand	Kleber
Tread pattern	Cropker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	46,00
Recommended rim size	7
Permitted rim size	8
Maximum air pressure [bar].	4,00
Section width (mm)	225
Outer diameter of tyre [mm].	1352
Stat. radius (SLR) [mm]	632
Rolling circumference [mm].	4035
Tread depth (mm)	31,0
Number of lugs	27x2
Tyre capacity 75% [ltr.]	87
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 A8	2060	40		4,00	
130 D	1900	65		4,00	