

## **TYRES**

| Product group   | Tyres          |
|-----------------|----------------|
| Item number     | 12426800       |
| Valid tyre size | 230 / 95 R 44  |
| LI / SI / PR    | 137 A8 / 134 D |
| TL/TT           | TL             |
| Brand           | Kleber         |
| Tread pattern   | Cropker        |





## Notes and features

- The Kleber Cropker is a premium crop tyre for tractors in the 80-200 hp performance range.
- Compared with its predecessor, the Kleber Super 3, the Cropker offers a higher load capacity and the double identifier D/A8.
- It can be used as a FRT (Free Rolling Tyre) on towed vehicles with with a load surcharge of up to 20% at 40 km/h.
- Thanks to the special root-friendly lug shoulders, plants in row crops are optimally protected.
- Its tread pattern reinforced in the centre of the tread provides improved driving and steering precision and longer mileage.
- Due to the shape of the lugs and the spaces between them, the tyre offers very good self-cleaning properties.



## **Technical Informations**

| Item number                  | 12426800       |
|------------------------------|----------------|
| EAN                          | 3528706252990  |
| Valid tyre size              | 230 / 95 R 44  |
| Alternative size 1           | 9.5R44         |
| LI / SI / PR                 | 137 A8 / 134 D |
| TL/TT                        | TL             |
| Brand                        | Kleber         |
| Tread pattern                | Cropker        |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | not necessary  |
| Nettogewicht [kg] (gültig)   | 55,00          |
| Recommended rim size         | 7              |
| Permitted rim size           | 8              |
| Maximum air pressure [bar].  | 4,00           |
| Section width (mm)           | 225            |
| Outer diameter of tyre [mm]. | 1556           |
| Stat. radius (SLR) [mm]      | 738            |
| Rolling circumference [mm].  | 4682           |
| Tread depth (mm)             | 31,0           |
| Number of lugs               | 31x2           |
| Tyre capacity 75% [ltr.]     | 102            |
| E-Ready                      | No             |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 137 A8 | 2300               | 40           |               | 4,00                        |              |
| 134 D  | 2120               | 65           |               | 4,00                        |              |