

## TYRES

|                 |                |
|-----------------|----------------|
| Product group   | Tyres          |
| Item number     | 12426804       |
| Valid tyre size | 270 / 95 R 44  |
| LI / SI / PR    | 145 A8 / 142 D |
| TL/TT           | TL             |
| Brand           | Kleber         |
| Tread pattern   | Cropker        |



**Kleber**

## Notes and features

- The Kleber Cropker is a premium crop tyre for tractors in the 80-200 hp performance range.
- Compared with its predecessor, the Kleber Super 3, the Cropker offers a higher load capacity and the double identifier D/A8.
- It can be used as a FRT (Free Rolling Tyre) on towed vehicles with with a load surcharge of up to 20% at 40 km/h.
- Thanks to the special root-friendly lug shoulders, plants in row crops are optimally protected.
- Its tread pattern reinforced in the centre of the tread provides improved driving and steering precision and longer mileage.
- Due to the shape of the lugs and the spaces between them, the tyre offers very good self-cleaning properties.

## Technical Informations

|                              |                |
|------------------------------|----------------|
| Item number                  | 12426804       |
| EAN                          | 3528706995323  |
| Valid tyre size              | 270 / 95 R 44  |
| Alternative size 1           | 11.2R44        |
| LI / SI / PR                 | 145 A8 / 142 D |
| TL/TT                        | TL             |
| Brand                        | Kleber         |
| Tread pattern                | Cropker        |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | not necessary  |
| Nettogewicht [kg] (gültig)   | 66,00          |
| Recommended rim size         | 9              |
| Permitted rim size           | 8, 10          |
| Maximum air pressure [bar].  | 4,00           |
| Section width (mm)           | 275            |
| Outer diameter of tyre [mm]. | 1632           |
| Stat. radius (SLR) [mm]      | 768            |
| Rolling circumference [mm].  | 4884           |
| Tread depth (mm)             | 34,0           |
| Number of lugs               | 28x2           |
| Tyre capacity 75% [ltr.]     | 144            |
| E-Ready                      | No             |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 145 A8 | 2900               | 40           |               | 4,00                     |              |
| 142 D  | 2650               | 65           |               | 4,00                     |              |