

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 12426804 |
| Valid tyre size | 270 / 95 R 44 |
| LI / SI / PR | 145 A8 / 142 D |
| TL/TT | TL |
| Brand | Kleber |
| Tread pattern | Cropker |



Kleber

Notes and features

- The Kleber Cropker is a premium crop tyre for tractors in the 80-200 hp performance range.
- Compared with its predecessor, the Kleber Super 3, the Cropker offers a higher load capacity and the double identifier D/A8.
- It can be used as a FRT (Free Rolling Tyre) on towed vehicles with with a load surcharge of up to 20% at 40 km/h.
- Thanks to the special root-friendly lug shoulders, plants in row crops are optimally protected.
- Its tread pattern reinforced in the centre of the tread provides improved driving and steering precision and longer mileage.
- Due to the shape of the lugs and the spaces between them, the tyre offers very good self-cleaning properties.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 12426804 |
| EAN | 3528706995323 |
| Valid tyre size | 270 / 95 R 44 |
| Alternative size 1 | 11.2R44 |
| LI / SI / PR | 145 A8 / 142 D |
| TL/TT | TL |
| Brand | Kleber |
| Tread pattern | Cropker |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 66,00 |
| Recommended rim size | 9 |
| Permitted rim size | 8, 10 |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 275 |
| Outer diameter of tyre [mm]. | 1632 |
| Stat. radius (SLR) [mm] | 768 |
| Rolling circumference [mm]. | 4884 |
| Tread depth (mm) | 34,0 |
| Number of lugs | 28x2 |
| Tyre capacity 75% [ltr.] | 144 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 145 A8 | 2900 | 40 | | 4,00 | |
| 142 D | 2650 | 65 | | 4,00 | |