

## TYRES

Product group	Tyres
Item number	12426848
Valid tyre size	IF 600 / 65 R 28
LI / SI / PR	160 D / 156 E
TL/TT	TL
Brand	Kleber
Tread pattern	Topker



**Kleber**

## Notes and features

- Large volume tyre for high-performance tractors.
- Optimally suitable for ploughing.
- Can be used with low inflation pressures.
- Very good traction.

## Technical Informations

Item number	12426848
EAN	3528706860287
Valid tyre size	IF 600 / 65 R 28
LI / SI / PR	160 D / 156 E
TL/TT	TL
Brand	Kleber
Tread pattern	Topker
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	160,00
Recommended rim size	DW21B (A)
Permitted rim size	DW20B (A)
Maximum air pressure [bar].	2,40
Section width (mm)	626
Outer diameter of tyre [mm].	1486
Stat. radius (SLR) [mm]	661
Rolling circumference [mm].	4417
Tread depth (mm)	52,0
Number of lugs	17x2
Tyre capacity 75% [ltr.]	405
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 D	4500	65		2,40	
156 E	4000	70		2,40	