

TYRES

Product group	Tyres	
Item number	12426848	
Valid tyre size	IF 600 / 65 R 28	
LI / SI / PR	160 D / 156 E	
TL/TT	TL	
Brand	Kleber	
Tread pattern	Topker	





Notes and features

- Large volume tyre for high-performance tractors.
- Optimally suitable for ploughing.

- Can be used with low inflation pressures.
- Very good traction.



Technical Informations

Item number	12426848
EAN	3528706860287
Valid tyre size	IF 600 / 65 R 28
LI / SI / PR	160 D / 156 E
TL/TT	TL
Brand	Kleber
Tread pattern	Topker
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	160,00
Recommended rim size	DW21B (A)
Permitted rim size	DW20B (A)
Maximum air pressure [bar].	2,40
Section width (mm)	626
Outer diameter of tyre [mm].	1486
Stat. radius (SLR) [mm]	661
Rolling circumference [mm].	4417
Tread depth (mm)	52,0
Number of lugs	17x2
Tyre capacity 75% [ltr.]	405
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 D	4500	65		2,40	
156 E	4000	70		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.