Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	12427170	
Valid tyre size	400 / 70 R 20	
LI / SI / PR	149 A8 / 149 B	
TL/TT	TL	
Brand	Kleber	
Tread pattern	Lugker	





Notes and features

- The Kleber Lugker is a tyre for telescopic handlers, wheel . loaders and backhoe loaders.
- The tread pattern design and lug angles provide good • traction, even on soft soil.
- Two belt plies protect the tyre from stabs and enable a • long service life of the tyre.
- The great rigidity of the sidewall guarantees the lowest • possible deformation under load and thus very good stability during lifting work.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	12427170
EAN	3528704783021
Valid tyre size	400 / 70 R 20
Alternative size 1	16.0/70R20
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	Kleber
Tread pattern	Lugker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	64,50
Recommended rim size	12SDC
Permitted rim size	13SDC
Maximum air pressure [bar].	4,00
Section width (mm)	412
Outer diameter of tyre [mm].	1062
Stat. radius (SLR) [mm]	480
Rolling circumference [mm].	3160
Tread depth (mm)	31,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	139
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		4,00	
149 B	3250	50		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.