

## TYRES

Product group	Tyres
Item number	12427170
Valid tyre size	400 / 70 R 20
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	Kleber
Tread pattern	Lugker



Bohnenkamp  
Moving Professionals

The Kleber logo, consisting of the word "Kleber" in a bold, black, sans-serif font. Above the letter "e" is a stylized red graphic element consisting of three parallel, slanted lines.

## Notes and features

- The Kleber Lugker is a tyre for telescopic handlers, wheel loaders and backhoe loaders.
- The tread pattern design and lug angles provide good traction, even on soft soil.
- Two belt plies protect the tyre from stabs and enable a long service life of the tyre.
- The great rigidity of the sidewall guarantees the lowest possible deformation under load and thus very good stability during lifting work.

**Technical Informations**

Item number	12427170
EAN	3528704783021
Valid tyre size	400 / 70 R 20
Alternative size 1	16.0/70R20
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	Kleber
Tread pattern	Lugker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	64,50
Recommended rim size	12SDC
Permitted rim size	13SDC
Maximum air pressure [bar].	4,00
Section width (mm)	412
Outer diameter of tyre [mm].	1062
Stat. radius (SLR) [mm]	480
Rolling circumference [mm].	3160
Tread depth (mm)	31,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	139
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		4,00	
149 B	3250	50		4,00	