

TYRES

Product group	Tyres
Item number	12427170
Valid tyre size	400 / 70 R 20
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	Kleber
Tread pattern	Lugker



Bohnenkamp
Moving Professionals

The Kleber logo, consisting of the word "Kleber" in a bold, black, sans-serif font. Above the letter "e" is a stylized red graphic element consisting of three parallel, slanted bars.

Notes and features

- The Kleber Lugker is a tyre for telescopic handlers, wheel loaders and backhoe loaders.
- The tread pattern design and lug angles provide good traction, even on soft soil.
- Two belt plies protect the tyre from stabs and enable a long service life of the tyre.
- The great rigidity of the sidewall guarantees the lowest possible deformation under load and thus very good stability during lifting work.

Technical Informations

Item number	12427170
EAN	3528704783021
Valid tyre size	400 / 70 R 20
Alternative size 1	16.0/70R20
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	Kleber
Tread pattern	Lugker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	64,50
Recommended rim size	12SDC
Permitted rim size	13SDC
Maximum air pressure [bar].	4,00
Section width (mm)	412
Outer diameter of tyre [mm].	1062
Stat. radius (SLR) [mm]	480
Rolling circumference [mm].	3160
Tread depth (mm)	31,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	139
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		4,00	
149 B	3250	50		4,00	