

TYRES

Product group	Tyres
Item number	12427190
Valid tyre size	460 / 70 R 24
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	Kleber
Tread pattern	Lugker





Notes and features

- The Kleber Lugker is a tyre for telescopic handlers, wheel loaders and backhoe loaders.
- The tread pattern design and lug angles provide good traction, even on soft soil.
- Two belt plies protect the tyre from stabs and enable a long service life of the tyre.
- The great rigidity of the sidewall guarantees the lowest possible deformation under load and thus very good stability during lifting work.



Technical Informations

Item number	12427190
EAN	3528709687225
Valid tyre size	460 / 70 R 24
Alternative size 1	17.5LR24
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	Kleber
Tread pattern	Lugker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	93,50
Recommended rim size	DW15L
Permitted rim size	DW14L, DW16L
Maximum air pressure [bar].	4,00
Section width (mm)	469
Outer diameter of tyre [mm].	1240
Stat. radius (SLR) [mm]	560
Rolling circumference [mm].	3704
Tread depth (mm)	34,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	217
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		4,00	
159 B	4375	50		4,00	