

TYRES

Product group	Tyres
Item number	12427195
Valid tyre size	500 / 70 R 24
LI / SI / PR	164 A8 / 164 B
TL/TT	TL
Brand	Kleber
Tread pattern	Lugker



Kleber

Notes and features

- The Kleber Lugker is a tyre for telescopic handlers, wheel loaders and backhoe loaders.
- The tread pattern design and lug angles provide good traction, even on soft soil.
- Two belt plies protect the tyre from stabs and enable a long service life of the tyre.
- The great rigidity of the sidewall guarantees the lowest possible deformation under load and thus very good stability during lifting work.

Technical Informations

Item number	12427195
EAN	3528702654613
Valid tyre size	500 / 70 R 24
Alternative size 1	19.5R24
LI / SI / PR	164 A8 / 164 B
TL/TT	TL
Brand	Kleber
Tread pattern	Lugker
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	107,00
Recommended rim size	DW16L
Permitted rim size	DW15L
Maximum air pressure [bar].	4,00
Section width (mm)	511
Outer diameter of tyre [mm].	1298
Stat. radius (SLR) [mm]	582
Rolling circumference [mm].	3830
Tread depth (mm)	34,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	264
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 A8	5000	40		4,00	
164 B	5000	50		4,00	