

TYRES

Product group	Tyres	
Item number	12500255	
Valid tyre size	16 x 6.50 - 8	
LI / SI / PR	64 A4, 4 PR	
TL/TT	TL	
Brand	Carlisle	
Tread pattern	Turf Trac R/S	



Notes and features

- Lawn tyre for all kinds of devices for professional lawn and landscape maintenance.
- Wide range of applications from zero-turn rotary mowers to utility vehicles.
- Tread design effectively protects green spaces.
- High tread depth guarantees longevity.



Technical Informations

Item number	12500255
EAN	5999110802169
Valid tyre size	16 x 6.50 - 8
Alternative size 1	170/60-8
LI / SI / PR	64 A4, 4 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	Turf Trac R/S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	2,90
Recommended rim size	5.375
Permitted rim size	4.25
Maximum air pressure [bar].	1,94
Section width (mm)	170
Outer diameter of tyre [mm].	406
Stat. radius (SLR) [mm]	182
Rolling circumference [mm].	1211
Tread depth (mm)	4,8
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
64 A4	280	16		1,90	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.