

TYRES

Product group	Tyres	
Item number	12500267	
Valid tyre size	16 x 6.50 - 8	
LI / SI / PR	73 A4, 6 PR	
TL/TT	TL	
Brand	Carlisle	
Tread pattern	Super Lug	



Notes and features

- Agricultural tyre for garden tractors, motor hoes and similar devices.
- Offers very good traction.



Technical Informations

Item number	12500267
EAN	5999110834528
Valid tyre size	16 x 6.50 - 8
Alternative size 1	170/60-8
LI / SI / PR	73 A4, 6 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	Super Lug
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	3,70
Recommended rim size	5.375
Permitted rim size	5.50A
Maximum air pressure [bar].	3,00
Section width (mm)	161
Outer diameter of tyre [mm].	422
Stat. radius (SLR) [mm]	188
Rolling circumference [mm].	1253
Tread depth (mm)	12,7
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
73 A4	365	20		3,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.