Bohnenkamp Moving Professionals

15.11.2024

TYRES

Product group	Tyres	
Item number	12500330	
Valid tyre size	18 x 9.50 - 8	
LI / SI / PR	81 A4, 4 PR	
TL/TT	TL	
Brand	Carlisle	
Tread pattern	Multi Trac C/S	



Notes and features

- Tyre for professional use on lawns, gardens and golf courses.
- Durable rubber compound in conjunction with deep tread blocks.
- Tread pattern optimised for stability and traction.

Bohnenkamp Moving Professionals

Technical Informations

Item number	12500330
EAN	5999110802817
Valid tyre size	18 × 9.50 - 8
Alternative size 1	240/55-8
LI / SI / PR	81 A4, 4 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	Multi Trac C/S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	5,20
Recommended rim size	7.00
Permitted rim size	7.001
Maximum air pressure [bar].	1,65
Section width (mm)	231
Outer diameter of tyre [mm].	457
Stat. radius (SLR) [mm]	204
Rolling circumference [mm].	1363
Tread depth (mm)	7,4
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
81 A4	462	20		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.