Bohnenkamp Moving Professionals

20.09.2024

TYRES

Product group	Tyres
Item number	12500364
Valid tyre size	21 x 11.00 - 8
LI / SI / PR	92 A4, 4 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	AT 101



Notes and features

- The Carlisle AT101 is small agricultural tyre for ZTR (Zeroturn) mowers and other vehicles.
- Its special lugs taper towards the shoulder area.
- The shape of the lugs and the shallow tread depth enable use on zero turn mowers that require extra traction.

Bohnenkamp Moving Professionals

Technical Informations

Item number	12500364
EAN	5999110802350
Valid tyre size	21 × 11.00 - 8
Alternative size 1	280/60-8
LI / SI / PR	92 A4, 4 PR
TL/TT	TL
Brand	Carlisle
Tread pattern	AT 101
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	7,80
Recommended rim size	8.50
Permitted rim size	7.00
Maximum air pressure [bar].	1,52
Section width (mm)	274
Outer diameter of tyre [mm].	533
Stat. radius (SLR) [mm]	238
Rolling circumference [mm].	1590
Tread depth (mm)	12,7
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
92 A4	630	20		1,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.